

## Product Data Sheet

### SUMITOMO EPDM

## **505A**

Ethylene Propylene Diene Rubber, Non-Oil Grade

Applications	Transfer and injection mouldings, for electrical equipment, sponge products for weather strips and heat insulation, and for ozone resistance modifier. Also suitable for wire and cable application, as well as for blend with diene type rubber.
Characteristics	Low Mooney Viscosity and high diene content, good flow and high cure rate, suitable for foam applications using continuous curing.

### Typical Properties

Characteristics		Value	Unit	Method
ML <sub>(1+4)</sub>	100°C	45	MU	ASTM D1646
Ethylene Content <sup>(*1)</sup>		57	wt%	ASTM D3900
ENB Content <sup>(*2)</sup>		8.4	wt%	ASTM D6047

The values shown are typical values measured on the product and are not to be considered as guaranteed specifications, actual test results may vary

(\*1) C<sub>2</sub> + C<sub>3</sub> = 100 wt%

(\*2) C<sub>2</sub> + C<sub>3</sub> + ENB = 100 wt%

**Manufacturer**

505A is manufactured in Saudi Arabia by Rabigh Refining & Petrochemical Co. (Petro Rabigh). The certification on ISO 9001, ISO 14001, and OHSAS 18001 is in progress and will be completed soon after commercial production.

**Regulatory Compliances**

Evaluation on common regulatory compliances on 505A will be verified by accredited third party laboratories soon after commercial production.

Please contact your nearest SCA representative for more information.

**Storage and Handling**

505A is supplied in 25kg bales in steel boxes. It is advisable to store in a well-ventilated storage facility, protected from rain, direct exposure to sunlight, temperature, and dust.

Moisture may accumulate inside the packaging if there is a significant fluctuation in ambient temperature and high relative humidity. If this occurs, customer is strongly advised to dry the resin prior to use. Direct exposure to sunlight and excessive ambient temperature may affect the properties, appearance, and odour characteristic of the resin. Please refer to the Safety Data Sheet (SDS) for information regarding industrial health and safety issues.

**Disposal and the Environment**

SCA prioritises environmental management in all our operations in responsibility and respect towards the community and the environment.

Disposal of 505A should at all times comply with the local and regional environmental protection and waste disposal regulations.

**Office Locations****SUMITOMO CHEMICAL ASIA PTE LTD**

3 Fraser Street, #07-28 DUO Tower, SINGAPORE 189352

Phone +65 6303 5188

Fax +65 6298 9621

Web Site [www.sumitomo-chem.com.sg](http://www.sumitomo-chem.com.sg)

**SUMIKA PLASTICS AND CHEMICALS TRADING (SHANGHAI) CO., LTD.**

Unit 46-07 Grand Gateway II, No.3 Hongqiao Road, Xu Hui District, Shanghai, CHINA 200030

Phone +86 21 6448 2255

Fax +86 21 6407 7365

**SUMIKA PLASTICS AND CHEMICALS TRADING (SHANGHAI) CO., LTD., GUANGZHOU BRANCH**

Room 6404, Office Building, CITIC Plaza, No.233, North Tianhe Road, Guangzhou City, CHINA 510613

Phone +86 20 3877 3577

Fax +86 20 3877 3511

**SCA SOUTH ASIA PETROCHEMICALS PRIVATE LIMITED**

Private Office No. 218, DBS Business Center, FF, World Trade Tower, Barakhamba Lane, Connaught Place, New Delhi 110001, INDIA

Phone +91 11 4050 9218

Fax +91 11 2341 4740

**SUMITOMO CHEMICAL EUROPE S.A./N.V.**

Woluwelaan, 57, B-1830 Machelen, BELGIUM

Phone +32 2 251 0650

Fax +32 2 251 2991

Web Site [sumitomochemicaleurope.eu](http://sumitomochemicaleurope.eu)

**SUMITOMO CHEMICAL EUROPE N.V.**

Turkey Liaison Office, Barbaros Mah. Cigdem Sok. No:1, Agaoglu My Office K:10, D:44-45, 34746 Bati Atasehir, Istanbul, TURKEY

Phone +90 216 680 3334

Fax +90 216 680 1012

**Disclaimer**

All information contained in this document is provided in good faith and its sole purpose is to provide information regarding SCA's polymer products. This product catalogue is provided on an "as is" basis. SCA makes no representation, warranty, express or implied and assumes no liability as to the accuracy or completeness of any of the information contained in this product catalogue. The values shown are purely values measured on the product and are not to be considered as guaranteed specifications. Any information on this product catalogue should not be considered as a recommendation. Customer is responsible to ensure that SCA materials, whether used alone or mix with other materials, are suitable for the intended application. SCA expressly disclaims for any and all liability, including direct and indirect loss, consequential loss or damages based on or relating to the use or errors of and omissions of such information in this product catalogue. Information contained herein is NOT intended to announce product availability anywhere in the world. Please contact your nearest SCA representative for more detailed information.